

Data sheet — WS2403-2






Item no. WS2403-2
Colour White

Geo data

Product ready to use		Product ready for dispatch		Packaging unit	
Length	9 cm	Length	13.3 cm	Length	37.5 cm
Width	8.6 cm	Width	10.5 cm	Width	28.5 cm
Height	2.5 cm	Height	3.4 cm	Height	24.5 cm
Weight	0.14 kg	Weight	0.22 kg	Weight	5 kg
Item EAN	4262379094912	Ready-to-ship packaging	×	PU GTIN	4262379094929
Units per pallet	1920			Quantity per PU	40

Attributes

The attributes specify the technical specifications of the product and provide detailed information about its features and performance data.

Area of Application	Indoor use
Memory Slots	1 alarm time
Operation	Buttons, Sensor-Touch
Degrees - Measuring Range	-10 – 50 °C

Degrees - Accuracy	± 1°C
Degrees - Read-Out Accuracy	1 °C
Display - Panel Type	LCD
Display - Signal Type	Digital
Display - Backlight Time	10 sec
Display - Width	70 mm
Display - Height	63 mm
Display - Digit Width	7 mm
Display - Digit Height	15 mm
Display - Backlight	temporary
Footprint Area - Width	5 cm
Footprint Area - Length	9 cm
Has Care Instructions - Available	✓
Has Warning Notice - Available	✓
Humidity - Measuring Range	20 – 95 %
Humidity - Accuracy	± 1%
Humidity - Read-Out Accuracy	1 %
Power Supply - Power Source	Battery
Recommended Area of Application	Human
Surface	matte
Time Settings	h, min

Materials

The material section provides information about the materials used and, where applicable, their proportions.

Housing	Plastic

Batteries

The batteries section provides information about the required battery types as well as, where applicable, the quantity and inclusion in the delivery.

Battery 1

Included	✓
Quantity	2
Size	AAA
Composition	Zinc-Carbon
Weight	11 g
Rated voltage	1.5 V
Discharge cutoff voltage	0.9 V
Max discharge current	1 A

Spare Parts

The spare parts section contains information about available spare and accessory parts that are sold separately.