Data sheet — CK2303

Digital radio-controlled alarm clock

The ADE CK2303 radio-controlled clock combines precision with extra-large display clarity. It shows time, indoor temperature (°C/°F), humidity, and date, with automatic or manual DCF time setting. Features include two alarm times, weekend mode, snooze, and a perpetual calendar in seven languages. Sensor-touch backlight, battery indicator, and flexible wall or tabletop placement complete the design.









Item no. CK2303
Colour Black



Item no. CK2303-1
Colour White

Geo data

Product ready to use		Product ready for dispatch		Packaging unit	
Length	18.8 cm	Length	19.7 cm	Length	41 cm
Width	9.1 cm	Width	10.5 cm	Width	32.5 cm
Height	4.8 cm	Height	6 cm	Height	34 cm
Weight	0.305 kg	Weight	0.38 kg	Weight	12.2 kg
Item EAN	4262379091232	Ready-to-ship packaging	×	PU GTIN	4262379091751
Units per pallet	780			Quantity per PU	30

Functions

The listed functions describe the special features and advantages of the product that distinguish it from other products and highlight its benefits for the user.

- 2 alarm times with snooze function
- Calendar with date display
- Display of temperature and humidity
- 2 x Alarm ON/OFF via slide switch
- Automatic and manual time setting
- 12/24 h display
- Non-slip base

Attributes

The attributes specify the technical specifications of the product and provide detailed information about its features and performance data.

Area of Application	Indoor use
Memory Slots	2 alarm times
Operation	Buttons, Sensor-Touch, Switches
Degrees - Measuring Range	-9.9 – 50 °C
Degrees - Accuracy	± 1°C
Degrees - Read-Out Accuracy	0.1 °C
Display - Panel Type	LCD
Display - Signal Type	Digital
Display - Backlight Time	10 sec
Display - Width	168 mm
Display - Height	73 mm
Display - Digit Width	23 mm
Display - Digit Height	46 mm
Display - Backlight	temporary
Foot Type	Silicone Feet
Has Care Instructions - Available	✓
Has Warning Notice - Available	✓
Humidity - Measuring Range	20 – 95 %
Humidity - Accuracy	± 1%

Humidity - Read-Out Accuracy	1 %
Instrument Types	Thermometer, Hygrometer, DCF
Power Supply - Power Source	Battery
Power Supply - Voltage	1.5 – 1.5 V
Recommended Area of Application	Human
Selectable Units	°C, °F
Surface	matte
Time Settings	h, min, sec

Materials

The material section provides information about the materials used and, where applicable, their proportions.

Housing	ABS Plastic

Batteries

The batteries section provides information about the required battery types as well as, where applicable, the quantity and inclusion in the delivery.

Battery 1

Size	AA
Composition	Zinc-Carbon
Weight	25 g
Rated voltage	1.5 V
Discharge cutoff voltage	0.9 V
Max discharge current	2 A
Included	✓
Consumer	Item
Quantity	2