Data sheet — WS1911

Weather station with projection

The ADE WS1911 weather station features animated forecasts, indoor/outdoor temperature and humidity (°C/°F, %), and a DCF radio-controlled clock with dual alarm and snooze. A backlit LCD display (94 × 63 mm) and 180° rotatable LED ceiling projection provide clear visibility. With date, weekday, and four brightness levels, it delivers practical climate data and modern convenience in one stylish device.









Item no. WS1911
Colour Black

Geo data

Product ready to use		Product ready for dispatch		Packaging unit	
Length	16.7 cm	Length	18 cm	Length	19.5 cm
Width	10 cm	Width	11 cm	Width	16.5 cm
Height	4 cm	Height	7.5 cm	Height	25 cm
Weight	0.295 kg	Weight	0.38 kg	Weight	1.68 kg
Item EAN	4260578582377	Ready-to-ship packaging	×	PU GTIN	4260578582384
Units per pallet	576			Quantity per PU	4

Functions

The listed functions describe the special features and advantages of the product that distinguish it from other products and highlight its benefits for the user.

- Projection display rotatable by 180°
- Animated weather forecast with trend indicator
- Comfort indicator
- Mould alert
- Display of temperature and humidity (indoor and outdoor)
- Min./Max. for temperature and humidity
- Frost alert
- Calendar with date display (DE, DK, EN, ES, FR, IT, NL)

Attributes

The attributes specify the technical specifications of the product and provide detailed information about its features and performance data.

Area of Application	Indoor
Memory Slots	2 alarm times
Operation	Buttons, Switches
Degrees - Measuring Range	-10 – 50 °C
Degrees - Accuracy	± 2°C
Degrees - Read-Out Accuracy	0.1 °C
Display - Panel Type	LCD
Display - Signal Type	Digital
Display - Backlight Time	15 sec
Display - Width	94 mm
Display - Height	63 mm
Display - Digit Width	11 mm
Display - Digit Height	21 mm
Display - Backlight	temporary
Footprint Area - Width	16.8 cm
Footprint Area - Length	4 cm
Has Care Instructions - Available	✓
Has Warning Notice - Available	✓
Humidity - Measuring Range	20 – 95 %
Humidity - Accuracy	± 5%
Humidity - Read-Out Accuracy	1 %

Instrument Types	Thermometer, Hygrometer, DCF
Power Supply - Power Source	Battery & AC
Recommended Area of Application	Human
Selectable Units	°C, °F
Surface	matte
Time Settings	h, min
Alarm - Mode	2 alarm times + weekend alarm
Alarm - Type	Audible
Alarm - Volume progression	Constant volume
Alarm - Signal pattern	Ascending sequence
Alarm - Key press sound	Not available
Weather station features - Climate features	Ventilation recommendation, Mold alert, Weather trend display, Comfort indicator, Animated weather forecast, Frost alert
Key press sound	Not available

Materials

The material section provides information about the materials used and, where applicable, their proportions.

Housing	ABS Plastic

Batteries

The batteries section provides information about the required battery types as well as, where applicable, the quantity and inclusion in the delivery.

Battery 1

Included	✓
Consumer	Item
Quantity	1
Size	CR2032
Composition	Lithium
Weight	4 g

Rated voltage	3 V
Discharge cutoff voltage	2 V
Max discharge current	0.3 A

Spare Parts

The spare parts section contains information about available spare and accessory parts that are sold separately.